# Ethernet Test System for Highly Efficient Conversion of BroadR-Reach™ Protocol

For all BroadR-Reach equipped systems that require conversion to Ethernet Customized software for easy debug and maintenance Link error diagnosis Easy-to-install and configure



## **PRODUCT DESCRIPTION**

BRidge4Net is a unique device in the market developed for converting 100BASE-TX (conventional Ethernet) to 100BASE-T1 (BroadR-Reach<sup>™</sup> Ethernet).

Featuring link error diagnosis, it is the ideal option for all test systems applications in the automotive industry and/or ATE's suppliers that require conversion to Ethernet.

### **KEY FEATURES**

Proprietary design and compact housing Customized software for debug and maintenance Mounting holes and flexible power input RJ45 connector for Ethernet and Molex connector for BroadR-Reach<sup>™</sup> API for LabView<sup>™</sup> / Teststand<sup>™</sup>

# **PRODUCT CONFIGURATION**

The stand-alone version is supplied inside a small box to be used in laboratory or bench. The bare version is supplied as a barebone PCB to be embedded in a JIG or test equipment. Both versions can be redesigned to meet specific space constraints or any other specific need.

- **1** / Simple to integrate and connect
- **2** / Convenient mounting holes
- **3** / Wide range power supply
- **4** / Easy installation, debug and maintenance

### **MAIN APPLICATIONS**

The careful design of the BRidge4Net converter makes it best suited for integration of high-end test systems for the automotive industry, such as radars, infotainment, and rear/front camera test systems. Examples include applications in climatic chambers; run-in, burn-in and any multi-DUT ATE, In-Circuit Testing, Functional Testing and Flash Programming.

# **TECH SPECS**

API Compatible with Labview<sup>™</sup>/Teststand<sup>™</sup>

Communication protocol / Ethernet PHY transceivers: MDIO / PC: USB

#### PHYs

/ Texas Instruments / 100BASE-TX: DP83822 / 100BASE-T1: DP83TC811

#### **Power supply**

/ DC barrel connector / Cable type/input: standard DC 2.5mm / Voltage: 9-36 VDC / Frequency: DC / Current: 1A

#### Inputs/Output

/ Ethernet connector: RJ45 / BroadR-Reach™ connector: Automotive Molex

Human-Machine Interface



01 PORTUGAL | 02 SPAIN | 03 GERMANY | 04 MEXICO | 05 MALAYSIA | 06 INDIA





